


Rückschlagventil

mit Sechskant

Non-return valve, with hexagon

Valvola di non ritorno F.F.



ITV	G	H	L		NI/min*
304051	M5	5,5	26,5	8	190
304052	G1/8	8,5	36,5	13	920
304053	G1/4	9	42,5	16	1600
304054	G3/8	12	51	20	2430
304055	G1/2	14	62	24	3500

* Ermittlung der Durchflusswerte bei 6 bar * Evaluation of flow rate at 6 bar * portata nominale a 6 bar

Körper:	CW614N vernickelt
Body:	CW614N nickel-plated
Corpo:	ottone CW614N nichelato
O-Ring:	NBR
O-ring:	NBR
O-Ring:	NBR 70 SH
zyl. Gewinde:	DIN EN ISO 228
cyl. Threads:	DIN EN ISO 228
Filettatura:	gas cilindrica ISO 228
Betriebstemperatur:	-10 °C bis +70 °C
Working temperature:	-10 °C up to +70 °C
Temperatura di esercizio:	da -10 °C a +70 °C
Betriebsdruck:	max. 10 bar
Working pressure:	max. 10 bar
Pressione di esercizio:	max. 10 bar
Für geölte und ungeölte Druckluft.	
For lubricated and non-lubricated compressed air.	
Per aria compressa sia lubrificata che non.	