


Sperrventil

pneumatisch gesteuert

Pneumatic operated blocking valve (double effect)

Valvola VIPazionata pneumaticamente doppio effetto



ITV	G	DN	A	ØB	L	E	P*	
580004	Rp3/8	10	53,8	46	98	30,8	10	22
580005	Rp1/2	15	60	51,7	112	33,3	10	27
580006	Rp3/4	20	70	63,5	135	38,25	10	33
580007	Rp1	25	76	69	143	41,5	10	41
580008	Rp1 1/4	32	91	86	165	48,25	10	50
580009	Rp1 1/2	40	102	96	180	53,75	10	60
580010	Rp2	50	115	109	207	59,75	10	70

* P = Druck [bar] * pressure [bar] * pressione [bar]

Betriebstemperatur: -20 °C bis +80 °C

Operating temperature: -20 °C to +80 °C

Temperatura di esercizio: da -20 °C a +80 °C

Steuerdruck: 4,2 - 8 bar

Air supply: 4,2 - 8 bar

Alimentazione dell'aria: 4,2 - 8 bar

Körper/Kolben: Messing vernickelt

Body/piston: brass nickel-plated

Corpo/pistone: ottone nichelato

Dichtung/O-Ring: NBR

Seal/O-ring: NBR

Guarnizione: NBR

Gewinde: ISO 7/1

Thread: ISO 7/1

Filettatura: ISO 7/1

Medien: Luft, Gas, Öl, Wasser, gefilterte Druckluft.

Media: Air, gas, oil, water, filtered compressed air.

Media: Aria, gas, olio, acqua, acqua, aria compressa filtrata.