


Mini-Kugelhahn 630

Mini ball valve 630

Valvola a sfera micro F/F cilindrica 630



ITV	G	H	L	D	E	DN		
63002	G1/8	8	36,5	19,5	21,5	5,5	14	-
63003	G1/4	11	43	19,5	21,5	5,5	14	-
63004	G3/8	11,5	46	19,5	23	8	18	-
63005	G1/2	15	56,5	26,5	33	10	22	-
63006	Rp3/4	16,3	67	26	33,5	14	28	30

Betriebstemperatur: -20 °C bis +80 °C

Operating temperature: -20 °C to +80 °C

Temperatura di esercizio: da -20 °C a +80 °C

Betriebsdruck: 20 bar

Inlet pressure: 20 bar

Pressione di esercizio: 20 bar

Körper/Kugel: Messing verchromt

Body/ball: brass chrome-plated

Corpo/sfera: ottone cromato

Griff: PA66

Handle: PA66

Leva: PA66

O-Ring: NBR 70

O-Ring: NBR 70

O-Ring: NBR 70

Gewinde: DIN EN ISO 228/ DIN EN ISO 10226

Thread: DIN EN ISO 228/ DIN EN ISO 10226

Filettatura: DIN EN ISO 228/ DIN EN ISO 10226

Einsatzgebiete: Luft-, Wasser-, Ölkreisläufe, Einsatz auch im mittleren bis niedrigen Vakuum möglich.

Applications: Air, Water and Oil dynamics circuits, use also in medium to low vacuum.

Campo di applicazione: Aria, acqua e circuiti oleodinamici; e' possibile l'utilizzo per medio/ basso vuoto pneumatico.