

## ipso 033

### Rückschlagverschraubung

Straight connection with non-return valve

Diritto maschio cilindrico con valvola di non ritorno con O-Ring



ITV	ØD	G	ØB	L	
203301	4	M5	8	42	9
203302	4	G1/8	13	35	11
203307	6	G1/8	13	39,0	13
203308	6	G1/4	16	38	14
203309	8	G1/8	13	38	15
203310	8	G1/4	16	40	16
203312	10	G1/4	16	42,5	18
203313	10	G3/8	20	42,5	18
203315	12	G1/2	25	46	22
203317	14	G1/2	25	52,5	25

Körper:	CW614N vernickelt
Body:	CW614N nickel-plated
Corpo:	ottone CW614N nichelato
O-Ring:	NBR
O-ring:	NBR
O-Ring:	NBR 70 SH
zyl. Gewinde:	DIN EN ISO 228
cyl. Threads:	DIN EN ISO 228
Filettatura:	gas cilindrica ISO 228
Betriebstemperatur:	-20 °C bis +80 °C
Working temperature:	-20 °C up to +80 °C
Temperatura di esercizio:	da -20 °C a +80 °C
Betriebsdruck:	0,2 - 10 bar
Working pressure:	0,2 - 10 bar
Pressione di esercizio:	da 0,2 a 10 bar
Für geölte und ungeölte Druckluft.	
For lubricated and non-lubricated compressed air.	
Per aria compressa sia lubrificata che non.	