


Drosselrückschlagventil mit Innengewinde

Typ B Abluft drosselbar
Unidirectional flow regulator type B for cylinders (female thread)
Regolatore di flusso unidirezionale per cilindro con anello femmina



ITV	G	H	L1	L2		NI/min*
304501	M5	4	25	11,5	8	45
304502	G1/8	5	32	21	14	310
304503	G1/4	6	37	25,5	17	450
304504	G3/8	6	46	26	20	1040
304505	G1/2	10	52,5	32	26	2200

* Ermittlung der Durchflusswerte bei 6 bar * Evaluation of flow rate at 6 bar * portata nominale a 6 bar

Körper:	CW617N vernickelt
Body:	CW617N nickel-plated
Corpo:	ottone CW617N nichelato
O-Ring:	NBR
O-ring:	NBR
O-Ring:	NBR 70 SH
Dichtungen:	Kunststoff
Seals:	Plastics
Rondella di tenuta sul filetto:	tecnopolimero
zyl. Gewinde:	DIN EN ISO 228
cyl. Threads:	DIN EN ISO 228
Filettatura:	gas cilindrica ISO 228
Betriebstemperatur:	-20 °C bis +70 °C
Working temperature:	-20 °C up to +70 °C
Temperatura di esercizio:	da -20 °C a +70 °C
Betriebsdruck:	max. 10 bar
Working pressure:	max. 10 bar
Pressione di esercizio:	max. 10 bar
Für geölte und ungeölte Druckluft.	
For lubricated and non-lubricated compressed air.	
Per aria compressa sia lubrificata che non.	