


Drosselrückschlagventil mit Ringstück

Typ A Zuluft drosselbar

Unidirectional flow regulator type A for valves

Regolatore di flusso unidirezionale per valvola con anello a calzamento



ITV	ØD	G	H	L1	L2	1	2	NI/min*
304105	5/3	M5	4	25	16	8	8	45
304100	5/3	G1/8	5	32	21	8	14	310
304106	6/4	M5	4	25	16	9	8	45
304101	6/4	G1/8	5,5	32	21,5	10	14	310
304102	6/4	G1/4	6	37	24,5	10	17	420
304103	8/6	G1/8	5	32	20,5	12	14	310
304104	8/6	G1/4	6	37	22,5	12	17	420
304109	10/8	G1/4	6	37	26,5	14	17	420
304110	10/8	G3/8	6,5	46	30,5	14	20	500

* Ermittlung der Durchflusswerte bei 6 bar * Evaluation of flow rate at 6 bar * portata nominale a 6 bar

Körper:	CW617N vernickelt
Body:	CW617N nickel-plated
Corpo:	ottone CW617N nichelato
O-Ring:	NBR
O-ring:	NBR
O-Ring:	NBR 70 SH
Dichtungen:	Kunststoff
Seals:	Plastics
Rondella di tenuta sul filetto:	tecnopolimero
zyl. Gewinde:	DIN EN ISO 228
cyl. Threads:	DIN EN ISO 228
Filettatura:	gas cilindrica ISO 228
Betriebstemperatur:	-20 °C bis +70 °C
Working temperature:	-20 °C up to +70 °C
Temperatura di esercizio:	da -20 °C a +70 °C
Betriebsdruck:	max. 10 bar
Working pressure:	max. 10 bar
Pressione di esercizio:	max. 10 bar
Für geölte und ungeölte Druckluft.	
For lubricated and non-lubricated compressed air.	
Per aria compressa sia lubrificata che non.	